

1 **Amendment To The Specification:**
2

3 Please amend the paragraph that begins on Page 7, Line 21 through Page 8, Line 10 as
4 follows:
5

6 A horizontally aligned movable platform 70 is positioned adjacent first sidewall 20. In
7 the first embodiment of the present invention single action mop wringer 10, the movable
8 platform 70 is movably supported by a pair of pivotable arms. The movable platform 70 and
9 pivotable arms are shown in greater detail in Figures 3 and 4. The movable platform 70 has a
10 horizontal top surface 72. First arm 76 has an elongated shaft 78 terminating in a base 80 having
11 a pair of pins 81 and 82 which are rotatably supported in a first bracket 84 affixed to the top
12 surface 72 of movable platform 70 and located adjacent one end of the movable platform 70.
13 The bracket 84 has a first wall 86 with an opening 87 to rotatably accommodate pin 81 and a
14 second wall 88 with an opening 89 to rotatably accommodate pin 82. At its opposite end,
15 elongated shaft 78 and first arm 76 terminate in a collar 90 having an opening 92. Second arm
16 96 also has an elongated shaft 98 terminating in a base 100 having a pair of pins 101 and 102
17 which are rotatably supporting second bracket 104 affixed to the top surface 72 of movable
18 platform 70 and located at the end of platform 70 opposite from the location of first bracket 84.
19 The second bracket 104 has a first wall 106 with an opening 107 to rotatably accommodate pin
20 101 and a second wall 108 with an opening 109 to rotatably accommodate pin 102. At its
21 opposite end shaft 98 of second arm 96 terminates in a collar 110 having an opening ~~122~~ 112.
22 Brackets 84 and 104 are parallel to each other so that arms 76 and 96 will rotate in the same
23 plane.
24
25
26
27
28